



## SPY6KiRTB

### Uniti Power Symphony

The Uniti Power Symphony 6kVA UPS series is engineered to support power loads of up to 6kVA/6kW, it can be configured as a rack or tower in a space-efficient manner. Equipped with high power density and true online double conversion technology, it offers reliable power protection. Furthermore, it comes with future-proof connectivity that allows for seamless integration with the cloud.

#### Key Features:

- ✓ 6kVA / 6kW
- ✓ Unity power factor
- ✓ Pure sine wave
- ✓ Online double conversion
- ✓ Hot swappable batteries
- ✓ Small footprint
- ✓ High efficiency
- ✓ IoT monitoring software
- ✓ Easy setup and safe connection to the cloud
- ✓ Real-time UPS monitoring to enable business continuity and failure prevention

### Peace of mind...

Uniti Power offers a standard six-year warranty on its Symphony UPS range and 2 years on the batteries. (UK only).



| Model name                       | SPY6KiRTB   |  |
|----------------------------------|---|--|
| Power rating                     | VA/Watt   | 6000VA/6000W   |
| Efficiency                       | Double conversion mode                                      | 95%  |
|                                  | ECO mode  | 98%  |
| Input performance                | Voltage range   | 160-275V 100% load, 110-160V derating to 50% load linearly   |
|                                  | Rated frequency   | 50Hz/60Hz  |
|                                  | Frequency range   | 40Hz-70Hz (45Hz-55Hz 54Hz-66Hz @ load>60%)   |
|                                  | PF  | >0.995   |
|                                  | THDI  | <3% linear load, <5% non linear load   |
| Input connection                 | L/N/PE hardware terminal connection                         |  |
| Output performance               | Rated voltage   | 220/230/240V   |
|                                  | Rated frequency   | 50Hz/60Hz  |
|                                  | Maximum PF  | 1  |
|                                  | Voltage accuracy  | ±1%  |
|                                  | THDv  | <1% linear load, <5% non linear load   |
|                                  | Transfer time   | 0ms (10ms @ ECO->Inverter)   |
|                                  | Crest Ratio   | Max 3:1  |
|                                  | Overload (line mode)  | 100% <load ≤105% continuous, 105% < load ≤125% for 10 minutes, 125 <load ≤150% for 30 seconds, >150% for 500ms |
| Output connection                | Wiring/socket   | L/N/PE hardware terminal connection  |
|                                  | Load segment control  | Optional   |
| Battery                          | Voltage   | 240VDC   |
|                                  | Capacity (AH)   | 20x12V/9Ah   |
|                                  | Backup time Typical value by default battery capacity, PF=1 | "2.1min 100% load, 8min 50% load"  |
| Max external battery modules     | 6   |  |
| Charger                          | Charging current  | 1.4A (0-4A adjustable)   |
|                                  | Recharging time   | 3h to 90%  |
| Other working mode               | CVCF  | Yes (derating to 60% load)   |
|                                  | Parallel  | Optional (up to 3)   |
| HMI<br>(human-machine interface) | Display   | Dot matrix LCD, rotatable manually   |
|                                  | Language  | 10 Languages   |
|                                  | USB   | USB 2.0 with HID   |
|                                  | RS232   | Yes (DB9)  |
|                                  | Dry in/out  | 1 programmable dry in; 1 programmable dry out  |
|                                  | EPO   | Yes  |
|                                  | Intelligent slot  | Yes (for long card)  |
|                                  | Network card  | Optional, NMC long card  |
|                                  | Modbus card   | Optional, CMC/Modbus Long Card   |
|                                  | Dry contactor card  | Optional, AS400 Long Card  |
|                                  | WLAN module   | Optional, HDMI type  |
| Physical performance             | Dimension (WxDxH) mm  | 5U height including 438x573x86.2 (power module, 2U), 438x593x129 (battery, 3U)                                 |
|                                  | IP protection level   | IP20   |
| Environment                      | Operating temperature                                       | 0-50°C (power derating to 50% @40-50°C )   |
|                                  | Relative Humidity   | 0-95%  |
|                                  | Operating Altitude  | 0-3000m (the load derating 1% every up 100m @1000-3000m)   |
|                                  | Acoustic Noise  | <50dB @ typical load with battery fully charge   |
| Certification                    | CE,IEC/EN 62040   |  |
| EMI                              | Conduction/Radiation  | C3   |
| EMS                              | ESD   | IEC/EN 61000-4-2   |
|                                  | RS232   | IEC/EN 61000-4-3   |
|                                  | EFT   | IEC/EN 61000-4-4   |
|                                  | Surge   | IEC/EN 61000-4-5   |
| Accessory                        | Input power cable   | N/A  |
|                                  | Output power cable  | N/A  |
|                                  | EBM cable   | Yes (in EBM)   |
|                                  | USB cable   | Yes  |
|                                  | RS232 cable   | Optional   |
|                                  | Rail kit  | Optional   |
|                                  | Tower feet  | Yes  |
|                                  | Rack ear  | Yes  |
| Manual                           | Yes   |  |



1. Input/output terminals
2. Battery port
3. Parallel port
4. Intelligent slot
5. WLAN, USB, RJ45, dry in/out
6. RS232
7. IoT monitoring QR code