

UPS  
Model:

## YP-Captuo

(6000 VA - 10000 VA)



Frequency	Phase	Power Factor	Power (VA)	Rated Voltage
45 / 70 Hz	1	1	6000 - 10000 VA	110 - 280 Vac

### Additional Information

- The YP-Captuo 6000-10000 VA single-phase online UPS provides exceptional protection and power availability, making it ideal for critical applications that demand extended uptime, scalability, and redundancy options.
- Scalable Power Solution: Up to 4 YP-Captuo 6000-10000 VA units can be connected in parallel, delivering a total output of 40 kVA. The redundancy configuration (3+1) supports up to 30 kVA, ensuring continuous load protection even in the event of a unit failure, as the fourth unit seamlessly takes over.
- Cost-Efficient Operation: The YP-Captuo UPS is designed with energy efficiency in mind, incorporating features that reduce operational costs by minimizing power consumption.
- Flexible Uptime Expansion: Increase uptime easily by adding external battery cabinets and additional battery chargers. Batteries can be replaced or expanded while the UPS is operational, ensuring uninterrupted power.
- Selective Load Protection: In the event of a network failure, the YP-Captuo UPS allows you to prioritize specific loads, providing them with longer runtime for continued operation.
- Reliable Device Protection: Connected devices are fully protected, and the UPS can be activated even when mains power is unavailable.
- Optimized for Sensitive Equipment: The YP-Captuo UPS is ideal for sensitive loads, such as medical devices, mass spectrometers, and forensic analyzers, and has minimal impact on generator fuel consumption.
- Automatic Restart & Shutdown Features: After a prolonged blackout, the UPS automatically restarts to power the connected load without operator intervention. The software also enables automated shutdown of devices for additional safety and control.

Unit 2, Hurricane Close, Sherburn in Elmet, Leeds, LS25 6PB, United Kingdom  
+44 1977 688155 • [sales@yorpower.com](mailto:sales@yorpower.com)

[www.yorpower.com](http://www.yorpower.com)

UPS  
Model:

## YP-Captuo

(6000 VA - 10000 VA)

MODEL		YP-Captuo 6000	YP-Captuo 10000	
<b>POWER</b>	VA	6000	10000	
	W	6000	1800	
<b>INPUT</b>	Rated Voltage	110 – 280 Vac		
	Frequency	45 – 70 Hz		
	Power factor	≥0.99		
<b>OUTPUT</b>	Rated Voltage	200/208/220/230/240 Vac selectable		
	Voltage distortion	≤2% with linear load, ≤7% with distorting load		
	Voltage stability	±1%		
	Frequency	50/60 Hz (selectable)		
	Frequency stability	≤0.2% (free running)		
	Power factor	1		
	Crest factor	03:01		
	Waverform	Pure sine wave		
	Output connection	Terminal blocks lockable		
<b>EFFICIENCY</b>	VFI mode	Up to 94%		
	ECO mode	Up to 98%		
<b>GENERAL</b>	Dimensions (WxDxH) mm	240 x 700 x 513	288 x 700 x 513	
	Weight (kg)	59	78	
	Arms	Audible and visual alarm alerts for: power failure, low battery, bypass transfer, and UPS fault.		
	Protection	Overload, overheating, short circuit, deep discharge, battery overcharging.		
	Operating mode	Multi-mode: VFI, ECO, Constant voltage constant frequency (CVCF) output.		
	Cold start from the battery without mains power	Included		
	Parallel connection	Up to 4 units for 3+1 redundancy		
<b>BATTERY</b>	Battery type	12V VRLA, AGM (maintenance-free lead)		
	Uptime with internal battery in minutes	50% load	12	11
		100% load	4	4
	Charging time (90%)	4 - 6 hours		
	Battery expansion module dimensions (WxDxH) mm **	288 x 663 x 661		
<b>ENVIRONMENTAL PARAMETERS</b>	Operating temperature**	0 – 40°C		
	Relative humidity	0 – 90% (without condensing)		
	Altitude (a.s.l.)	<1000 m with no power derating, >1000 m with 1% derating for every 100 m.		
	Audible noise at 1 m	<60 dBA		
<b>CONNECTIVITY</b>	Built-in communication ports	USB, RS232, EPO, remote On/Off contact, and additional slots for optional cards		
	User interface	LCD and function keys (parameters: voltage, frequency, percentage load, battery voltage, output voltage, estimated uptime, UPS temperature).		
	Optional accessories	Cards: SNMP, RS485 ModBus, dry relay contacts		
	Compatible software platforms	Microsoft Windows, Linux, Mac OS, Vmware		
<b>REGULATIONS</b>	Standards	IEC EN 62040-1, IEC EN 62040-2, IEC EN 62040-3		
	Marking	CE, UKCA		

Unit 2, Hurricane Close, Sherburn in Elmet, Leeds, LS25 6PB, United Kingdom  
+44 1977 688155 • sales@yorpower.com

[www.yorpower.com](http://www.yorpower.com)