

Genset
Model:

YXP60RSC & RS

X-Series

Enclosed set



Open Set



*** The images are for illustration purposes only.*

Frequency	Phase	Power Factor	Prime Output	Standby
50Hz	3	0.8	60 kVA / 48 kW	66 kVA / 53 kW

Ratings

- Prime output: This rating is applicable for supplying continuous electrical power at variable load. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.
- Standby output: This rating is applicable for supplying electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings.
- Standard reference conditions: 25°C, 100m A.S.L., 30% relative humidity.

Design Features

- High quality assembly, providing stiffness and low vibration.
- Powder coated canopy. Corrosion and scratch resistant.
- Compact and long service life.
- Wiring and connectors with double protection.
- Protection guards in radiator and high voltage parts.
- Full 12 month YorPower warranty.

Design Standards

- CE marking
- ISO8528.5
- GB/T2820.5
- ISO 9001

Configuration

- 4-Stroke water-cooled diesel engine.
- Industrial silencer.
- Single bearing, 4 pole brushless alternator.
- Anti vibration mountings.
- Integral fuel tank with bunded base protection.
- Auto start control system with electronic digital control module DSE4520.
- Output circuit breaker.
- Emergency stop button.
- High engine temperature and low oil pressure shutdown system.
- 12V starter battery with leads and switch.

Acoustic canopy features

- Water and dust proof design.
- Door locks.
- High quality sound absorbing and fire retardant inner material.
- Lifting lugs.
- Forklift holes in base.

Unit 2, Hurricane Close, Sherburn in Elmet, Leeds, LS25 6PB, United Kingdom
+44 1977 688155 • sales@yorpower.com

www.yorpower.com


Engine data

Engine brand	Perkins	Total coolant capacity	10.2 Litres
Engine model	1103A-33TG2	Total lube oil capacity	7.9 Litres
Engine speed	1500 RPM	Bore	105 mm
Cylinders	3	Stroke	127 mm
Aspiration	Turbocharged	Compression ratio	17.25 : 1
Combustion system	Direct injection	Fuel cons. @ 110% standby load	15.4 l/hr
Displacement	3.3 Litres	Fuel cons. @ 100% Prime load	13.9 l/hr
Governor type	Mechanical	Fuel cons. @ 75% Prime load	10.4 l/hr
Cooling System	Water	Fuel cons. @ 50% Prime load	7.2 l/hr

Alternator data


Alternator brand	Leroy Somer	Winding pitch	2/3
Alternator model	TAL042-H	Number of wires	6
Excitation	SHUNT	AVR	R120
Insulation class	H	Voltage regulation	± 1%
Drip proof protection	IP23	Power Factor	0.8

Enclosed set data



L X W x H (mm)	Weight	Fuel tank	Noise@7M
2338 x 1080 x 1551	1332 kg	165 Litres	68.1 dBA

Open set data



** The images are for illustration purposes only.

L X W x H (mm)	Weight	Fuel tank	Noise@7M
1827 x 809 x 1384	886 kg	220 Litres	N/A

Unit 2, Hurricane Close, Sherburn in Elmet, Leeds, LS25 6PB, United Kingdom
+44 1977 688155 • sales@yorpowers.com

www.yorpowers.com