

Genset Model:

YXP900RSC & RS

X-Series

Enclosed set



Open Set



** The images are for illustration purposes only.

Frequency	Phase	Power Factor	Prime Output	Standby
50Hz	3	0.8	900 kVA / 720 kW	990 kVA / 792 kW

Ratings

- Prime output: This rating is applicable for supplying continuous electrical power at variable load. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.
- Standby output: This rating is applicable for supplying electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings.
- Standard reference conditions: 25°C, 100m A.S.L., 30% relative humidity.

Design Features

- High quality assembly, providing stiffness and low vibration.
- Powder coated steel. Corrosion and scratch resistant.
- · Compact and long service life.
- Wiring and connectors with double protection.
- Protection guards in radiator and high voltage parts.
- Full 12 month YorPower warranty.

Design Standards

- CE marking
- ISO8528.5
- GB/T2820.5
- ISO 9001

Configuration

- 4-Stroke water-cooled diesel engine.
- Industrial silencer.
- Single bearing, 4 pole brushless alternator.
- Anti vibration mountings.
- Integral fuel tank with fully bunded base protection. (enclosed unit only).
- Fuel level sensor (enclosed set only).
- Auto start control system with electronic digital control module DSE7420.
- Output circuit breaker.
- Emergency stop button.
- High engine temperature and low oil pressure shutdown system.
- 24V starter battery with leads and switch.

Acoustic canopy features

- Water and dust proof design.
- · Door locks.
- High quality sound absorbing and fire retardant inner material.
- · Lifting lugs.

Unit 2, Hurricane Close, Sherburn in Elmet, Leeds, LS25 6PB, United Kingdom +44 1977 688155 • sales@yorpower.com

www.yorpower.com



Engine data

Engine brand			
Engine model			
Engine speed			
Cylinders			
Aspiration			
Combustion system			
Displacement			
Governor type			
Cooling System			

Perkins
4008TAG1A
1500 RPM
8
Turbocharged and air-to-air charge cooled
Direct injection
30.561 Litres
Electronic
Water-cooled

Total coolant capacity		
Total lube oil capacity		
Bore		
Stroke		
Compression ratio		
Fuel cons. @ 110% standby load		
Fuel cons. @ 100% Prime load		
Fuel cons. @ 75% Prime load		
Fuel cons. @ 50% Prime load		

143 Litres
153 Litres
160 mm
190 mm
13.6:1
218 l/hr
195 l/hr
143 l/hr
98 l/hr

Alternator data


Alternator brand			
Alternator model			
Excitation			
Insulation class			
Drip proof protection			

Leroy Somer
TAL049-D
SHUNT
Н
IP23

Winding pitch			
Number of wires			
AVR			
Voltage regulation			
Power Factor			


2/3	
6	
R150	
± 0.8%	
0.8	

Enclosed set data



	LXWxH(mm)	Weight	Fuel tank	Noise@7M
6058 x 2438 x 2728		10872 kg	1150 Litres	79.2 dBA

Open set data



** The images are for illustration purposes only.

LXWxH(mm)	Weight	Fuel tank	Noise@7M
5119 x 2134 x 2435	6565 kg	N/A	N/A

Unit 2, Hurricane Close, Sherburn in Elmet, Leeds, LS25 6PB, United Kingdom +44 1977 688155 • sales@yorpower.com

www.yorpower.com