

Product Specifications For P18-6

Generator Set Specifications

| | |
|--------------------------------|---|
| Minimum Rating | 16.5 kVA / 13.2 kW |
| Maximum Rating | 22 kVA / 17.6 kW |
| Emissions/Fuel Strategy | EUIIIa Emissions Compliant |
| 50 Hz Prime | 16.5 kVA / 13.2 kW |
| 50 Hz Standby | 18 kVA / 14.4 kW |
| 60 Hz Prime | 20 kVA / 16 kW |
| 60 Hz Standby | 22 kVA / 17.6 kW |
| Frequency | 50 / 60 Hz |
| Speed | 1500 or 1800 RPM |
| Voltage | 220-415 Volts |
| 50 Hz Prime Rating | These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours. |
| 60 Hz Prime Rating | These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3). |
| 50 Hz Standby Rating | Standard reference conditions 25°C (77°F) Air Inlet Temp, 100m (328 ft) A.S.L. 30% relative humidity. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2. |

Engine Specifications

| | |
|--------------------------|---------------------|
| Engine Model | Perkins® 404D-22G1 |
| Bore | 84 mm (3.3 in) |
| Stroke | 100 mm (3.9 in) |
| Governor Type | Mechanical |
| Displacement | 2.2l (135.2 cu. in) |
| Compression Ratio | 23.3:1 |

P18-6 Standard Equipment

Engine

- Air Cleaner
- Lube oil drain valve
- Engine filled with lubrication oil
- High Coolant Temperature Shutdown
- Low Oil Pressure Shutdown

Cooling

- Package mounted radiator
- Radiator & Cooling Fan
- Coolant Drain Valve
- Fan, Fan drive and battery charging Alternator drive fully guarded to meet EC Machinery Directive
- Cooling System filled with Coolant mix

Exhaust

- Exhaust flange outlet
- Exhaust stub pipe and gasket

Fuel

- 8 Hr Fuel Tank or Skidbase
- Fuel Fittings for Local and Remote Feed

Alternator

- FG Wilson Alternator
- SHUNT Excitation
- IP23 Protection

Control Panel

FG100

Mounting

Base, Formed Steel with Skid base or Single wall Fuel Tank
Certified Base Mounted Lifting Eyes, and Rear Drag Eyelets
Anti-vibration mounts
Battery Tray and Cables

P18-6 Optional Equipment

Exhaust

Industrial, Residential, Critical Silencers

Alternator

Leroy Somer Alternator
Quadrature Droop Kit
Anti-Condensation Heater and Panel Circuitry

Control Panels

DSE4520
DSE7320
DSE7410
Deep Sea DSE7420

Starting/Charging

Lead Acid battery (Dry)

General

Upgrade to Standard Set for "CE" Certification
EEC Declaration of Conformity
Narrow, Wide or Skid Base
Sound attenuated, steel or galvanised enclosure
Dual wall fuel tanks

Enclosure

Compliance to European Community Directive 2000/14/EC
Super sound attenuation for residential areas
Totally enclosed exhaust silencing system
Robust and highly corrosion resistant construction